

Interior decoration coating

Composition and properties Destination

Powder coating with a base of lime, other quarry products and binder JES 010. The paste obtained after mixing is white.

- Decoration for walls, floors, wet areas (showers and bathrooms), furniture
- New construction and renovation.

Classification

European ecological classification pending. Classification M1 on M1 support, M0 on M0 support

FEATURES

Appearance when bagged

White powder + white liquid JES 010

Density

1.2 kg / L

VOC

Not applicable

Appearance of the film

Smooth

Yield

From 150gr/m² per coat on smooth surfaces to 300gr/m² per coat depending on the flatness and absorbency of the support.

Drying time

(At 20 °C and 65% RH)

At least 3 hours in the open air. Reduced drying time depending on ambient temperature.

Storage

12 months in original unopened packaging
Store away from frost and moisture.

Product preparation

See instructions for use.

Application equipment

Rounded stainless steel plaster's trowel or stainless steel or plastic stucco trowel, brush.

Cleaning of tools

With water after use.

Application conditions

In conformity with DTU 59.1

Supports

Condition and quality in conformity with DTU 59.1

Surface Preparation

See instructions for use.

Application system

In accordance with the rules of the art and DTU 59.1

Health and safety

According to DTU 59.1. See our application data sheets for each finish.

Product not classified as dangerous. Consult the safety data sheet.

The physico-chemical data given in this sheet are for the white product. The indicated VOC value represents the value of the product ready for use, after addition of colouring, dilution, etc., with our range of products. In no case can we be held responsible for mixes made with other commercial products, for which we do not know the actual VOC content. This technical data sheet is intended to inform our customers about the properties of our product. The information contained in it is based on our present state of knowledge. We invite our customers to check the suitability of the product, the nature of the supports and to undertake representative sampling tests. It is the responsibility of our customers to check that the present data sheet has not been replaced or modified by a later edition